

WHAT IS CLAIMED IS:

~~1. An optical transmission system transmitting a~~
plurality of electrical signals via an optical transmission path
after frequency division multiplexing, said system comprising:

a plurality of amplitude modulation parts for receiving
5 each corresponding transmitting data, and amplitude-modulating
carriers of differing frequencies by the transmitting data;

a frequency division multiplex part for receiving a
resultant amplitude modulated signal from each of said amplitude
modulation parts, and multiplexing said amplitude modulated
10 signals and outputting a frequency division multiplex signal;

an intensity modulation part for intensity modulating an
optical signal by said frequency division multiplex signal, and
outputting the intensity-modulated optical signal to said optical
transmission path;

15 an external modulation part for intensity modulating said
intensity-modulated optical signal this time by an electrical
signal equal in frequency to any one of the carriers used in said
plurality of amplitude modulation parts; and

an optical-electrical conversion part for converting, by
20 square detection, said optical signal provided by said external
modulation part into an electrical signal.

~~2. The optical transmission system according to claim 1,~~

05740813.122100

wherein

said transmitting data includes digital data, and

said plurality of amplitude modulation parts each include

5 a digital amplitude modulation part for subjecting the carriers of differing frequencies to digital amplitude modulation by said digital data.

3. The optical transmission system according to claim 1, further comprising means for extracting, from the electrical signal obtained by conversion in said optical-electrical conversion part, any one transmitting data desired.

4. The optical transmission system according to claim 1, wherein said external modulation part includes a semiconductor optical amplifier.

5. The optical transmission system according to claim 4, wherein

said transmitting data includes digital data, and

said plurality of amplitude modulation parts each include

5 a digital amplitude modulation part for subjecting the carriers of differing frequencies to digital amplitude modulation by said digital data.

6. The optical transmission system according to claim 4,

~~further comprising means for extracting, from the electrical signal obtained by conversion in said optical-electrical conversion part, any one transmitting data desired.~~

7. An optical transmission system transmitting a plurality of electrical signals via an optical transmission path after frequency division multiplexing, said system comprising:

a plurality of optical transmission parts for each transmitting an optical signal varied in optical frequency;

an optical multiplex part for receiving and multiplexing said optical signals, and outputting a resultant optical signal to said optical transmission path; and

an optical separation part for separating the optical signal coming through said optical transmission path into a plurality of optical signals based on an optical frequency;

for each of said optical signals obtained through separation,

an external modulation part for intensity modulation by an electrical signal of predetermined frequency; and

an optical-electrical conversion part for converting said optical signal provided by said external modulation part, by square detection, into an electrical signal, and

said plurality of optical transmission parts each comprise:

a plurality of amplitude modulation parts for receiving each corresponding transmitting data, and

amplitude-modulating carriers of differing frequencies by the transmitting data;

25 a frequency division multiplex part for receiving a resultant amplitude modulated signal from each of said amplitude modulation parts, and multiplexing said amplitude modulated signals outputting a frequency division multiplex signal; and

30 an intensity modulation part for intensity modulating an optical signal by said frequency division multiplex signal, and outputting the intensity-modulated optical signal to said optical transmission path.

8. The optical transmission system according to claim 7, wherein

5 said transmitting data includes digital data, and said plurality of amplitude modulation parts each include a digital amplitude modulation part for subjecting the carriers of differing frequencies to digital amplitude modulation by said digital data.

9. The optical transmission system according to claim 7, further comprising means for extracting, from the electrical signal obtained by conversion in said optical-electrical conversion part, any one transmitting data desired.

10. An optical transmission system transmitting a

~~plurality of electrical signals via an optical transmission path~~

after frequency division multiplexing, said system comprising:

a plurality of amplitude modulation parts for receiving
5 each corresponding transmitting data, and amplitude-modulating
carriers of differing frequencies by the transmitting data;

a frequency division multiplex part for receiving a
resultant amplitude modulated signal from each of said amplitude
modulation parts, and multiplexing said amplitude modulated
10 signals and outputting a frequency division multiplex signal;

an intensity modulation part for intensity modulating an
optical signal by said frequency division multiplex signal, and
outputting the intensity-modulated optical signal to said optical
transmission path; and

15 an optical-electrical conversion part for converting, by
square detection, said optical signal provided by said external
modulation part into an electrical signal, wherein,

superposed on a bias voltage or a bias current of said
optical-electrical conversion part is an electrical signal whose
20 frequency is equal to any one of the carriers used in said plurality
of amplitude modulation parts.

11. The optical transmission system according to claim 10,
wherein

said transmitting data includes digital data, and
said plurality of amplitude modulation parts each include

5 ~~a digital amplitude modulation part for subjecting the carriers~~
of differing frequencies to digital amplitude modulation by said
digital data.

12. The optical transmission system according to claim 10,
further comprising means for extracting, from the electrical
signal obtained by conversion in said optical-electrical
conversion part, any one transmitting data desired.

13. An optical transmission system transmitting a
plurality of electrical signals via an optical transmission path
after frequency division multiplexing, said system comprising:

5 a plurality of amplitude modulation parts for receiving
each corresponding transmitting data, and amplitude-modulating
carriers of differing frequencies by the transmitting data;

a frequency division multiplex part for receiving a
resultant amplitude modulated signal from each of said amplitude
modulation parts, and multiplexing said amplitude modulated
10 signals and outputting a frequency division multiplex signal;

a light source for outputting light constant in intensity;

a first SSB modulation part for SSB (Single SideBand)
modulating said light by said frequency division multiplex signal,
and outputting a resultant optical signal to said optical
15 transmission path;

an optical filter part for receiving the optical signal

coming through said optical transmission path, and from the optical signal, extracting an optical carrier component and an optical sideband component;

20 a second SSB modulation part for SSB modulating said optical sideband component by an electrical signal whose frequency is equal to any one of the carriers used in said plurality of amplitude modulation parts;

25 an optical combining part for combining said optical carrier component with a resultant optical signal obtained through SSB modulation in said second SSB modulation part; and

an optical-electrical conversion part for converting, by square detection, a resultant optical signal coming from said optical combining part into an electrical signal.

14. The optical transmission system according to claim 13, wherein

said transmitting data includes digital data, and

5 said plurality of amplitude modulation parts each include a digital amplitude modulation part for subjecting the carriers of differing frequencies to digital amplitude modulation by said digital data.

15. The optical transmission system according to claim 13, further comprising means for extracting, from the electrical signal obtained by conversion in said optical-electrical

conversion part, any one transmitting data desired.

16. An optical transmission system transmitting a plurality of electrical signals via an optical transmission path after frequency division multiplexing, said system comprising:

a plurality of amplitude modulation parts for receiving
5 each corresponding transmitting data, and amplitude-modulating carriers of differing frequencies by the transmitting data;

a frequency division multiplex part for receiving a resultant amplitude modulated signal from each of said amplitude modulation parts, and multiplexing said amplitude modulated
10 signals and outputting a frequency division multiplex signal;

a light source for outputting light constant in intensity;

a first SSB modulation part for SSB modulating said light by said frequency division multiplex signal, and outputting a resultant optical signal to said optical transmission path;

15 an optical filter part for receiving the optical signal coming through said optical transmission path, and from the optical signal, extracting an optical carrier component and an optical sideband component;

a second SSB modulation part for SSB modulating said optical
20 carrier component by an electrical signal whose frequency is equal to any one of the carriers used in said plurality of amplitude modulation parts;

~~an optical combining part for combining said optical~~

~~sideband component with a resultant optical signal obtained~~

25 through SSB modulation in said second SSB modulation part; and

an optical-electrical conversion part for converting, by square detection, a resultant optical signal coming from said optical combining part into an electrical signal.

17. The optical transmission system according to claim 16, wherein

said transmitting data includes digital data, and

5 said plurality of amplitude modulation parts each include a digital amplitude modulation part for subjecting the carriers of differing frequencies to digital amplitude modulation by said digital data.

18. The optical transmission system according to claim 16, further comprising means for extracting, from the electrical signal obtained by conversion in said optical-electrical conversion part, any one transmitting data desired.

19. An optical transmission system transmitting a plurality of electrical signals via an optical transmission path after frequency division multiplexing, said system comprising:

5 a plurality of optical transmission parts for each transmitting an optical signal varied in optical frequency; an optical multiplex part for receiving and multiplexing

~~Said optical signals, and outputting a resultant optical signal~~
to said optical transmission path;

an optical filter part for receiving the optical signal
10 coming through said optical transmission path, and from the
optical signal, extracting an optical carrier component and an
optical sideband component;

a second SSB modulation part for SSB modulating said optical
sideband component by an electrical signal of predetermined
15 frequency;

an optical combining part for combining said optical
carrier component with a resultant optical signal obtained
through SSB modulation in said second SSB modulation part; and

an optical-electrical conversion part for converting, by
20 square detection, a resultant optical signal coming from said
optical combining part into an electrical signal, and

said plurality of optical transmission parts each comprise:

a plurality of amplitude modulation parts for
receiving each corresponding transmitting data, and
25 amplitude-modulating carriers of differing frequencies by the
transmitting data;

a frequency division multiplex part for receiving a
resultant amplitude modulated signal from each of said amplitude
modulation parts, and multiplexing said amplitude modulated
30 signals and outputting a frequency division multiplex signal;

a light source for outputting light constant in

intensity, and

a first SSB modulation part for SSB modulating said light by said frequency division multiplex signal.

20. The optical transmission system according to claim 19, wherein

said transmitting data includes digital data, and

said plurality of amplitude modulation parts each include a digital amplitude modulation part for subjecting the carriers of differing frequencies to digital amplitude modulation by said digital data.

21. The optical transmission system according to claim 19, further comprising means for extracting, from the electrical signal obtained by conversion in said optical-electrical conversion part, any one transmitting data desired.

22. The optical transmission system according to claim 19, wherein said optical filter part comprises an optical filter which shows periodicity to wavelength, and a variable wavelength filter which passes only light of desired wavelength and can be varied in band for passing.

23. The optical transmission system according to claim 22, wherein

~~said transmitting data includes digital data, and~~

5 said plurality of amplitude modulation parts each include
a digital amplitude modulation part for subjecting the carriers
of differing frequencies to digital amplitude modulation by said
digital data.

24. The optical transmission system according to claim 22,
further comprising means for extracting, from the electrical
signal obtained by conversion in said optical-electrical
conversion part, any one transmitting data desired.

25. An optical transmission system transmitting a
plurality of electrical signals via an optical transmission path
after frequency division multiplexing, said system comprising:

5 a plurality of optical transmission parts for each
transmitting an optical signal varied in optical frequency;

an optical multiplex part for receiving and multiplexing
said optical signals, and outputting a resultant optical signal
to said optical transmission path;

10 an optical filter part for receiving the optical signal
coming through said optical transmission path, and from the
optical signal, extracting an optical carrier component and an
optical sideband component;

a second SSB modulation part for SSB modulating said optical
carrier component by an electrical signal of predetermined

15 frequency;

an optical combining part ~~for combining said optical~~
sideband component with a resultant optical signal obtained
through SSB modulation in said second SSB modulation part; and

an optical-electrical conversion part for converting, by
20 square detection, a resultant optical signal coming from said
optical combining part into an electrical signal, and

said plurality of optical transmission parts each comprise:

03740813.122400
25 a plurality of amplitude modulation parts for
receiving each corresponding transmitting data, and
amplitude-modulating carriers of differing frequencies by the
transmitting data;

30 a frequency division multiplex part for receiving a
resultant amplitude modulated signal from each of said amplitude
modulation parts, and multiplexing said amplitude modulated
signals and outputting a frequency division multiplex signal;

a light source for outputting light constant in
intensity; and

a first SSB modulation part for SSB modulating said
light by said frequency division multiplex signal.

26. The optical transmission system according to claim 25,
wherein

said transmitting data includes digital data, and
said plurality of amplitude modulation parts each include

5 ~~a digital amplitude modulation part for subjecting the carriers~~
of differing frequencies to digital amplitude modulation by said
digital data.

27. The optical transmission system according to claim 25,
further comprising means for extracting, from the electrical
signal obtained by conversion in said optical-electrical
conversion part, any one transmitting data desired.

28. The optical transmission system according to claim 25,
wherein said optical filter part comprises an optical filter which
shows periodicity to wavelength, and a variable wavelength filter
which passes only light of desired wavelength and can be varied
5 in band for passing.

29. The optical transmission system according to claim
28, wherein

said transmitting data includes digital data, and

said plurality of amplitude modulation parts each include

5 a digital amplitude modulation part for subjecting the carriers
of differing frequencies to digital amplitude modulation by said
digital data.

30. The optical transmission system according to claim 28,
further comprising means for extracting, from the electrical

Signal obtained by conversion in said optical-electrical conversion part, any one transmitting data desired.

31. An optical receiver for reproducing any desired electrical signal from an optical signal intensity modulated by a frequency division multiplex signal having a plurality of amplitude-modulated electrical signals multiplexed thereon, said receiver comprising:

an external modulation part for intensity modulating said optical signal by an electrical signal of predetermined electrical signal; and

an optical-electrical conversion part for converting, by square detection, said optical signal provided by said external modulation part into an electrical signal.

32. An optical receiver for reproducing any desired electrical signal from an optical signal intensity modulated by a frequency division multiplex signal having a plurality of amplitude-modulated electrical signals multiplexed thereon, said receiver comprising:

a local oscillation signal source for outputting an electrical signal of a predetermined frequency; and

an optical-electrical conversion part for converting said optical signal into an electrical signal by square detection,

wherein

~~superposed on a bias voltage or a bias current of said~~
optical-electrical conversion part is the electrical signal from
said local oscillation signal source.

33. An optical receiver for reproducing any desired
electrical signal from an optical signal SSB (Single SideBand)
modulated by a frequency division multiplex signal having a
plurality of amplitude-modulated electrical signal multiplexed
thereon, said receiver comprising:

an optical filter part for extracting an optical carrier
component and an optical sideband component from said optical
signal;

an SSB modulation part for SSB modulating said optical
sideband component by an electrical signal of predetermined
frequency;

an optical combining part for combining said optical
carrier component with a resultant optical signal SSB modulated
by said SSB modulation part; and

an optical-electrical conversion part for converting, by
square detection, said SSB-modulated optical signal into an
electrical signal.

34. An optical receiver for reproducing any desired
electrical signal from an optical signal SSB (Single SideBand)
~~modulated by a frequency division multiplex signal having a~~

~~Plurality of amplitude-modulated electrical signal multiplexed~~

5 thereon, said receiver comprising:

an optical filter part for extracting an optical carrier component and an optical sideband component from said optical signal;

10 an SSB modulation part for SSB modulating said optical carrier component by an electrical signal of predetermined frequency;

an optical combining part for combining said optical sideband component with a resultant optical signal SSB modulated by said SSB modulation part; and

15 an optical-electrical conversion part for converting, by square detection, said SSB-modulated optical signal into an electrical signal.

35. An optical receiver for reproducing any desired electrical signal from a multiplexed optical signal which is structured by a plurality of optical signals SSB (Single SideBand) modulated by a frequency division multiplex signal having a
5 plurality of amplitude-modulated electrical signal multiplexed thereon, said receiver comprising:

an optical filter part for extracting, from said multiplexed optical signal, an optical carrier component and an optical sideband component of one of said plurality of optical
10 signals;

~~an SSB modulation part for SSB modulating said optical~~
sideband component by an electrical signal of predetermined
frequency;

an optical combining part for combining said optical
15 carrier component with a resultant optical signal SSB modulated
by said SSB modulation part; and

an optical-electrical conversion part for converting, by
square detection, said SSB-modulated optical signal into an
electrical signal.

36. The optical receiver according to claim 35, wherein
said optical filter part comprises an optical filter which shows
periodicity to wavelength, and a variable wavelength filter which
passes only light of desired wavelength and can be varied in band
5 for passing.

37. An optical receiver for reproducing any desired
electrical signal from a multiplexed optical signal which is
structured by a plurality of optical signals SSB (Single SideBand)
modulated by a frequency division multiplex signal having a
5 plurality of amplitude-modulated electrical signal multiplexed
thereon, said receiver comprising:

an optical filter part for extracting, from said
multiplexed optical signal, an optical carrier component and an
~~optical sideband component of one of said plurality of optical~~

10 signals;

an SSB modulation part for SSB modulating said optical carrier component by an electrical signal of predetermined frequency;

15 an optical combining part for combining said optical sideband component with a resultant optical signal SSB modulated by said SSB modulation part; and

an optical-electrical conversion part for converting, by square detection, said SSB-modulated optical signal into an electrical signal.

38. The optical receiver according to claim 37, wherein said optical filter part comprises an optical filter which shows periodicity to wavelength, and a variable wavelength filter which passes only light of desired wavelength and can be varied in band
5 for passing.

add
a1